
DELTA®-REFLEX


100 % Air and Vapor-Tight!



Saves Energy and Cuts Costs.

DELTA®-REFLEX

10 % Energy Savings. 50 % Heat Reflection. 100 % Air- and Vapor-tight.









- Enhances thermal insulation by up to 10 %.
- Shields 30 % hazardous electromagnetic radiation.
- Achieves 50 % heat reflectance as certified by Fraunhofer Institute in Freiburg/ Germany.
- Creates 100 % air- and vaportight seal.
- Excellent fire resistance. Conform to strict B1 rating as per DIN 4102.
- Perfect air- and vapor-tight seal at all seams and connections joined with DELTA®-POLY-TAPE and DELTA®-FLEXX-BAND.
- Outstanding tensile strength due to its built-in reinforcement grid.
- Class I vapor barrier.
- Outstanding flexibility allows for fast and easy installation.

■ DELTA®-REFLEX PLUS with the integrated self-adhesive edge provides even more energy savings and faster airtight installation.

Technical Data Overview:	
Material	Vaportight, corrosion-proof aluminium layer laminated between transparent polyester film and grid-reinforced polyethylene film.
Application	High performance vapor barrier.
Fire behaviour	High fire resistance, B1 rating/DIN 4102
Tensile strength	apprx. 450 N/5 cm according to DIN 12311 in both directions
Perm Rating	<0.1 perms
Temperature range	-40 °C to +80 °C
Weight	apprx. 180 g/m²
Roll weight	apprx. 13.5 kg
Roll sizes	50 m x 1.5 m

Not designed for permanent UV exposure. Always cover as soon as possible.



You are sure to appreciate these handy DELTA®-Accessories:



DELTA®-MULTI-BAND

All-round adhesive tape for sealing of overlaps and openings, and repairing



DELTA®-FLEXX BAND

Stretchable sealing tape for inner and outer connections to structural details such as skylights, dormer windows, ventilator exhaust pipes, cables etc.



DELTA®-POLY-TAPE

Aluminized adhesive tape for sealing of overlapping DELTA®-REFLEX sheets. Or – as an alternative – use DELTA®-REFLEX PLUS with the integrated self-adhesive edge.





Dörken Systems Inc. 4655 Delta Way Beamsville, ON LOR 1B4, Canada Tel.: +1 (905) 563 3255 Fax: +1 (905) 563 5582 info@dorken.com www.dorken.com

A DÖRKENGROUP company

The information printed in this brochure reflects product information and specifications at the date of printing. The manufacturer reserves the right to make changes when necessary. All rights reserved.

DELTA®-branded quality products manufactured by Dörken.

Visit us on:















