



3M™ Ultra Conformable Flashing Tape 3015UC

Technical Data

October 2019

Product Description 3M™ Ultra Conformable Flashing Tape 3015UC is a proprietary 3M detailing tape designed for the commercial construction market to be used in conjunction with a 3M™ Commercial Air Barrier System. It is constructed with a unique 3M backing that allows up to 370% elongation in multiple directions, enabling contractors to detail windows and other complex penetrations up to 40% faster by not having to cut and splice multiple pieces of tape.

3M acrylic adhesive allows the application of 3M™ Ultra Conformable Flashing Tape 3015UC at temperatures as low as -18°C (0°F) and as high as 66°C (150°F). 3M™ Ultra Conformable Flashing Tape 3015UC can be exposed to UV sunlight for up to 12 months. It is repositionable, yet will adhere to and accept adhesion from most common building substrates per criteria of AAMA 711-13 using test method ASTM C-794.

Product Construction	Adhesive	Colour	Tape Thickness w/o liner
	High Performance Acrylic	Translucent Grey	1 mm (38 mils)

- Features**
- Provides internal strength and durability
 - Nail Sealability: Passes ASTM E331/547 per AAMA 711-13, Annex both before and after thermal cycling.
 - Strong multi-directional tape stretches and conforms to difficult areas
 - Easy, fast and hassle-free installation
 - Service temperature from -40° to 150°C (-40° to 300°F).
 - Can be applied to substrates from -18° to 66°C (0° to 150°F).
 - Resists UV exposure for up to 12 months
 - Translucent for visual inspection
 - Compatible with the most common building and construction substrates

- Application Ideas**
- Sealing around rough openings and joints in commercial building applications
 - Sealing of through wall flashing penetrations such as ducts, conduits, cables and pipes
 - Conforms to all dimensions of through wall penetrations openings within building envelopes such as around electrical cables, chimneys etc. to prevent air/moisture and water intrusion

3M™ Ultra Conformable Flashing Tape 3015 UC

Performance
Characteristics

90° peel, jaw speed 30.5 cm (12 inch)/min (ASTM D3330).

Initial Peel Strength (24 hr. dwell @ 22.2 °C [72 °F])	
Adhesion to Steel	130 N/100 mm (22.0 Lbs/inch)
Adhesion to Concrete Based Material	130 N/100 mm (22.5 Lbs/inch)
Adhesion to OSB	100 N/100 mm (22.5 Lbs/inch)
Adhesion to Wood	100 N/100 mm (22.5 Lbs/inch)
Adhesion to Exterior Grade Gypsum Board	*19.4 N/100 mm (4.3 Lbs/inch)
Peel Strength after Aging (7 days @ 22.2 °C [72 °F] & 50% RH)	
Adhesion to Steel	150 N/100 mm (33.0 Lbs/inch)
Adhesion to Concrete Based Material	140 N/100 mm (31.5 Lbs./inch)
Adhesion to OSB	110 N/100 mm (24.7 Lbs./inch)
Adhesion to Wood	140 N/100 mm (31.5 Lbs./inch)
Adhesion to Exterior Grade Gypsum Board	* 21.3 N/100 mm (4.8 Lbs/inch)

* Separated fibreglass facer mat from gypsum core.

Tensile Stress at break Elongation at break ASTM D-412	4.2 PSI (0.840 N/mm ²) ≥ 300 %
--	---

3M™ Ultra Conformable Flashing Tape 3015 UC

Technical Notes

- To obtain the best adhesion, 3M™ Ultra Conformable Flashing Tape 3015UC should be applied when temperatures range from -18°C (0°F) up to 66°C (150°F) over clean surfaces that are free from dirt and debris and have not absorbed water.
- Surfaces should be free of any damaged, unsupported areas, sharp protrusions or voids.
- Concrete must be cured a minimum of 7 days before application.
- While it can be applied as low as -18°C (0°F) surfaces must be clear of snow, ice or frost.
- Must be lapped a minimum of 5 cm (2 in) with air barrier
- Adheres to most common building materials. For difficult-to-stick-to surfaces, test adhesion before application. If needed, apply 3M™ Hi-Strength 90 Spray Adhesive, 3M™ Hi-Strength 94ET Spray Adhesive, 3M™ Holdfast 70 Spray Adhesive or 3M™ Fastbond™ Contact Adhesive 30NF to prime the substrate prior to applying the membrane. Products are available as either an aerosol or cylinder spray adhesive.

Application

- Fill gaps and cracks exceeding 0.6 cm (¼ in) width with 3M™ Polyurethane Sealant 540 or 3M™ Polyurethane Construction Sealant 525, and tool the surface flush and smooth.
- Fill gaps exceeding 1.3 cm (½ in) width with closed cell foam backer rod, seal with 3M™ Polyurethane Sealant 540 or 3M™ Polyurethane Construction Sealant 525, and tool the surface flush and smooth.

3M™ Ultra Conformable Flashing Tape 3015 UC

Storage Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original carton.

Shelf Life To obtain best performance, use this product within 24 months from date of manufacture.

Technical Information The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy and Disclaimer Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

ISO 9001

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.



Industrial Adhesives and Tapes Division
3M Canada
P.O. Box 5757
London, ON N6A 4T1

1 800 364-3577
3M.ca/AirBarrier